

SAFETY DATA SHEET

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME	LUCITE® XL
Product Description	Clear and opaque coloured sheet. A high molecular weight acrylic sheet used in a wide range of applications. Polymethylmethacrylate: greater than 90%.
Grades covered	XL Solid, Granite, Marble, Serenity Series, Gemstone, Lustre, Lustre Marble.
CAS No.	25852-37-3
Recommended uses and restrictions on use	Surface material for sanitary ware (bath, shower, sinks, spas)
Manufacturer	LUCITE INTERNATIONAL, Inc., 7275 Goodlett Farms Parkway, Cordova, TN 38016-4909 Phone: 1-800-4-LUCITE msdsinfo@lucite.com
Emergency Phone No.	1-800-424-9300 (Transport Emergency) 1-877-886-2143 (Medical Emergency)

2. HAZARDS IDENTIFICATION

Hazard classification	Not Classified as Dangerous for Supply/Use.
Other hazards	Low toxicity under normal conditions of handling and use. Combustion or thermal decomposition will evolve toxic, irritant and flammable vapors. Care should be taken during thermoforming to ensure that the product is not exposed to temperatures exceeding 200°C. Certain machining operations eg laser cutting, can give rise to toxic and corrosive fumes. Adequate ventilation MUST be used.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical identity of the substance Poly(Methyl methacrylate/Butyl acrylate)
CAS No. 25852-37-3

Substance identity	%W/W	CAS No.
Poly(Methyl methacrylate/Butyl acrylate)	~97	25852-37-3
Methyl methacrylate	~1	80-62-6
Dibutyl phthalate	>0.1	84-74-2

4. FIRST AID MEASURES

Description of first aid measures	
Inhalation	Dust or fumes from fabrication operations may cause irritation. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
Skin Contact	Unlikely to cause skin irritation. IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical attention.
Eye Contact	Dust or fumes from fabrication operations may cause irritation. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Ingestion	Low oral toxicity Do not induce vomiting. Rinse mouth.
Most important symptoms and effects, both acute and delayed	Not applicable.
Indication of any immediate medical attention and special treatment needed	None necessary.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	Water spray, foam, dry powder or CO ₂ .
Special hazards arising from the substance or mixture	Combustion will evolve toxic, irritant and flammable vapors.
Special protective equipment and precautions for fire fighters	A self contained breathing apparatus and suitable protective clothing should be worn in fire conditions.

6. ACCIDENTAL RELEASE MEASURES

Methods and materials for containment and cleaning up	Offcuts, swarf or dust should be collected and disposed of in a safe way.
Other advice	See Section: 8, 13

7. HANDLING AND STORAGE

HANDLING	These sheets are heavy and unwieldy. They should be handled with care, particularly in windy locations or outdoors. If broken or chipped the resultant edges can be sharp and cause cuts to skin and eyes. Take precautionary measures against static discharges.
Process Hazards	All polymers degrade to some extent at their processing temperature, an effect which increases with increasing temperature. Under normal conditions where thermoforming temperatures will not exceed 200°C thermal decomposition products will include Methyl methacrylate and Dibutyl phthalate. Local exhaust ventilation and/or respiratory protective equipment should be used. Certain machining operations eg laser cutting, can give rise to toxic and corrosive fumes. Adequate ventilation MUST be used.
STORAGE	Keep away from heat. Store vertically on A-frames.
Storage Temperature	<40°C
Storage Life	Indefinite under specified storage conditions.
Incompatible materials:	Most organic solvents , Acetone , chlorinated hydrocarbons .

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

The following values apply to substances which may be evolved during thermal processing.

Substance	CAS No.	OSHA PEL TWA	ACGIH TWA	ACGIH STEL	Company Std. TWA	Company Std. STEL
Methyl methacrylate	80-62-6	100 ppm	50 ppm	100 ppm	50 ppm	100 ppm
n-Butyl acrylate	141-32-2	Not established.	10 ppm			
Dibutyl phthalate	84-74-2	5 mg/m ³	5 mg/m ³			

Appropriate engineering controls	Do not eat, drink or smoke at the work place. Provide adequate ventilation, including appropriate local extraction if dusts, fumes or vapors are likely to be evolved. Consideration should be given to the work procedures involved and the potential extent of exposure as they may determine whether a higher level of protection is required. Local extraction close to the cutting head must be used when laser cutting. When thermoforming local exhaust ventilation should be used. Where suitable engineering controls are not fitted or are inadequate, wear suitable protective equipment. The following information is given as general guidance.
----------------------------------	--

Individual protection measures, such as personal protective equipment (PPE)

Eye/face protection



Wear eye/face protection. Safety spectacles/goggles/full face shield.

Skin protection



Wear suitable gloves. Sharp edges may cause cuts.

Respiratory protection



NORMAL HANDLING : Not normally required.

PROCESSING: Dust: A suitable dust mask or dust respirator with filter type P may be appropriate. (EN141/EN143).

Vapor: If high levels above the Occupational Exposure Limit are likely a suitable mask with filter type A may be appropriate (EN141/EN143).

9. PHYSICAL AND CHEMICAL PROPERTIES

Form	Sheet
Color.	Clear or colored
Odour	Odorless.
Specific Gravity	1.19
Solubility (Water)	Insoluble.
Solubility (Other)	Soluble in most organic solvents, acetone and chlorinated hydrocarbons

10. STABILITY AND REACTIVITY

Chemical Stability	Stable under normal conditions.
Hazardous Reactions	None known.
Conditions to avoid	Keep away from heat.
Materials to avoid	Most organic solvents , Acetone , chlorinated hydrocarbons .
Hazardous Decomposition Product(s)	Methyl methacrylate, Butyl acrylate, Carbon dioxide, Carbon monoxide, traces of Acrolein.

11. TOXICOLOGICAL INFORMATION

Acute toxicity	
Ingestion	Unlikely to be hazardous if swallowed.
Inhalation	Unlikely route of exposure.
Skin Contact	No evidence of irritant effects from normal handling and use. Sharp edges may cause cuts.
Eye Contact	Swarf or dust may cause irritation. Sharp off-cuts may cause eye damage.

12. ECOLOGICAL INFORMATION

This environmental hazard assessment is based on information available on similar products.

Ecotoxicity	The product is predicted to have low toxicity to aquatic organisms.
Persistence and degradability	The product is non-biodegradable in soil. There is no evidence of degradation in soil and water.
Bioaccumulative potential	The product has low potential for bioaccumulation.
Mobility	The product has low mobility in soil.

13. DISPOSAL CONSIDERATIONS

The waste is considered to be non hazardous. Large quantities of waste may be recoverable. Contact supplier for specialised advice.

Disposal methods	Disposal should be in accordance with local, state or national legislation. May be disposed of by landfill in accordance with local regulations. Incineration may be used to recover energy value.
------------------	--

14. TRANSPORT INFORMATION

DOT (DEPARTMENT OF TRANSPORTATION)	Not applicable
UN No.	Not applicable
Class	Not applicable.
Packing group	Not applicable
Environmental hazards	Not applicable.
Special precautions for user	Not applicable.
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.

15. REGULATORY INFORMATION

US Federal Regulations

Superfund reportable discharge	None
SARA 302 - Extremely Hazardous Substances	None

US State Regulations

California	SUBSTANCES KNOWN TO THE STATE OF CALIFORNIA TO CAUSE BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM : Dibutyl phthalate Proposition 65 (California) : Dibutyl phthalate
------------	--

Canadian Regulations

WHMIS Classification	None
----------------------	------

EU regulations

Safety, health and environmental regulations	This product is an Article and as such Article 31 (Requirements for Safety Data Sheets) of Regulation (EC) No 1907/2006 does not apply. REACH: This product contains Dibutyl phthalate (>0.1% w/w).
--	--

16. OTHER INFORMATION

The following sections contain revisions or new statements:	1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16
Date of preparation:	07 -August- 2013

Inventory Status

European Union	All chemicals in this product comply with REACH regulations.
United States (TSCA)	Listed in TSCA
Canada (DSL/NDL)	Listed in DSL
Japan (ENCS)	Listed in ENCS
Philippines (PICCS)	Listed in PICCS
Australia (AICS)	Listed in AICS
South Korea (KECI)	Listed in KECI
China (IECSC)	Listed in IECSC

LEGEND

Note: Not all of the following are necessarily contained in this Safety Data Sheet:

LTEL: Long Term Exposure Limit

STEL: Short Term Exposure Limit

TWA: Time Weighted Average

PEL: Permissible Exposure Levels

OSHA: Occupational Safety and Health Administration

SARA: Superfund Amendments and Reauthorization Act

WHMIS: Worker Hazardous Materials Information System

LUCITE® is the Registered Trade Mark of companies within the Lucite International Limited Group of companies.

For other technical information, contact the address in Section 1.

Lucite International does not recommend this product for use in applications involving long-term contact with body tissues.

It is the responsibility of the end-product manufacturer to identify all market and use-specific regulations and to ensure compliance with these regulations.

Subject to the exclusions and limitations set out below the Information contained in this publication or as otherwise supplied to the User is believed to be accurate and has been given in good faith. It is for the User to use the Information contained in this publication or as otherwise supplied to the User with care and satisfy itself of the suitability of the product for their intended use and the applicability of the advice given. Except to the extent that exclusion is prevented by applicable law Lucite International Inc. gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded and accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.